

NAUTILUS

FLOORING SPECS

NAUTILUS SPECIFICATIONS

Dimensions:	12mm thick + 2mm pad x 5"W x 48" L
Wear Layer:	AC3
Profile:	4-Sided Micro Bevel
Warranty:	25yr Residential, 5yr Light Commercial
Packaging:	19.77 sf/ctn, 12 pcs/ctn, 44 ctn/plt, 869.9 sf/plt
Installation:	Angle/Drop
Coordinating Trim:	End Cap, Quarter Round, Reducer, Stair Nose and T-mold Available

NAUTILUS WIDE SPECIFICATIONS

Dimensions:	12mm thick + 2mm pad x 7.5"W x 48" L
Wear Layer:	AC3
Profile:	4-Sided Micro Bevel
Warranty:	25yr Residential, 5yr Light Commercial
Packaging:	12.8 sf/ctn, 5 pcs/ctn, 65 ctn/plt, 832 sf/plt
Installation:	Angle/Drop
Coordinating Trim:	End Cap, Quarter Round, Reducer, Stair Nose and T-mold Available



(Hydro Systems Only)



Up to 72hrs



Up to 4000sf



NAUTILUS & NAUTILUS WIDE TRIMS

NAUTILUS

TRIM PROFILES & MEASUREMENTS

TRIM DESCRIPTION

QUARTER ROUND

Applied to cover the expansion gap between the flooring and the wall.

END CAP

Often times called Square Edge or Threshold, used when butting up to carpet or a sliding glass door.

T-MOLD

Joins two floors of equal height, such as in a doorway, between two rooms or in a large area where the maximum length/width is exceeded.





STAIR NOSE

Ends flooring at the top of either a landing or downward staircase.

REDUCER

Ends the flooring onto a surface such as concrete.

TRIM PROFILE



TRIM DIMENSIONS

