

SPECIFICATIONS

Dimensions:	
<i>Foundations</i>	7" Wide x 48.6" Long x 4.2mm thick
<i>Harmony</i>	9" Wide x 60" Long x 6.2mm thick
<i>Harmony Multi-Width</i>	5/7/9" Wide x 60" Long x 6.2mm thick
<i>Sonata</i>	4.25" Wide x 48.6" Long x 6.2mm thick
Packaging:	
<i>Foundations</i>	26.02 sf/ctn, 11 pcs/ctn, 60 ctn/plt
<i>Harmony</i>	18.6 sf/ctn, 5 pcs/ctn, 48 ctn/plt
<i>Harmony Multi-Width</i>	23.02 sf/ctn, 8 pcs/ctn, 26 ctn/plt
<i>Sonata</i>	20.1 sf/ctn, 14 pcs/ctn, 48 ctn/plt
Finish:	
<i>Foundations</i>	12mil Wearlayer, Polyurethane Coating, Embossed
<i>Sonata/Harmony</i>	22mil Wearlayer, Polyurethane Coating, Embossed
Warranty:	
<i>Foundations</i>	25 Yr Residential/Multi-Family, 5 Yr Commercial
<i>Sonata/Harmony</i>	Lifetime Residential/Multi-Family, 15 Yr Commercial
Installation:	
Tightlock Angle/Drop/Tap	
Coordinating Trim:	
Quarter Round, Multi Reducer, T-mold, Flush Stairnose, Overlap Stairnose	

TEST METHOD & REQUIREMENTS

Resilient Floor in Modular Format With Rigid Polymeric core	ASTM F3261	Pass
Dimensional Stability & Curling	ASTM F2199/ISO 23999	Pass
Length & Width Tolerance	ISO 24337	Pass
Thickness Tolerance	ASTM F387	Pass
Squareness	ISO 24337	Pass
Flatness	ISO 24337	Pass
Residual Indentation	ASTM F1914	Pass
Static Load	ASTM F970/ASTM F387	Pass
Resistance to Chemicals	ASTM F925	Pass
Resistance to Heat	ASTM F1515	Pass
Resistance to light	ASTM F1514	Pass
Residual Indentation	ASTM F1914	Pass
Dimensional Stability	ASTM F2199	Pass
Static Coefficient of Friction	ASTM D2047	Pass
Fire Resistance (CHF)	ASTM E648/NFPA 253	Pass
Smoke Density	ASTM E662	Pass
IIC	69	

