

# CALYPSO

## FLOORING SPECS

### Features/Benefits

ArtoGuard Core: Water Resistant up to 72 Hours

AC4 Wearlayer: Durable in All Environments

1.5mm Attached Pad: Luxury Comfort Underfoot

Painted Micro Bevel: Realistic and Dimensional Appearance

### Specifications

<b>Dimensions:</b>	13.5mm thick overall x 6.5" wide x 48" length (12mm core plus 1.5mm pad)
<b>Wearlayer:</b>	AC4
<b>Profile:</b>	4-Sided Painted Micro Bevel
<b>Warranty:</b>	Lifetime Residential, 15-yr Light Commercial
<b>Packaging:</b>	15.25 sf/ctn, 7 pcs/ctn, 45 ctn/plt, 686.38 sf/plt
<b>Installation:</b>	Angle/Drop & Tap - Titan Triple Lock
<b>Coordinating Trim:</b>	End cap, Quarter Round, Reducer, Stair Nose and T-mold Available
<b>IIC Rating:</b>	58



Up to 72hrs



(Hydronic Systems Only)



# CALYPSO

## TRIMS

### TRIM DESCRIPTION

#### QUARTER ROUND

Applied to cover the expansion gap between the flooring and the wall.

#### END CAP

Often times called Square Edge or Threshold, used when butting up to carpet or a sliding glass door.

#### T-MOLD

Joins two floors of equal height, such as in a doorway, between two rooms or in a large area where the maximum length/width is exceeded.






#### STAIR NOSE

Ends flooring at the top of either a landing or downward staircase.

#### REDUCER

Ends the flooring onto a surface such as concrete.

### TRIM PROFILE



### TRIM DIMENSIONS

